This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDER'S
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.



WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:		(11) International Publication Number: WO 95/05743
A21D 6/00, 13/02	A1	(43) International Publication Date: 2 March 1995 (02.03.95
(21) International Application Number: PCT/US: (22) International Filing Date: 2 August 1994 (DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
(30) Priority Data: 08/111,998 25 August 1993 (25.08.93)	t	Published With international search report.
71) Applicant: THE PILLSBURY COMPANY [US/L South Sixth Street, Minneapolis, MN 55402 (US).		
(72) Inventors: RABE, Gerald, O.; 5724 Lake Rose Dri netonka, MN 55345 (US). MEYERS, Thomas, A.; Box 2, Parker Prairie, MN 56361 (US).		
(74) Agent: BRUESS, Steven, C.; Merchant, Gould, Smit Welter & Schmidt, 3100 Norwest Center, 90 South Street, Minneapolis, MN 55402 (US).		

(54) Title: HIGH RATIO BAKING COMPOSITION

(57) Abstract

A high ratio baking composition comprising: (a) a chlorine free heat treated soft flour; (b) an effective volume controlling amount of a non-flour fiber; (c) an effective fragility controlling amount of a protein; and (d) sugar wherein the density of a baked product resulting from the high ratio baking composition is less than about 5.6 to 6.3 g/in³ and the weight ratio of the sugar to the heat treated soft flour is at least about 1:1.

١,

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	· GB	United Kingdom	MR	Mauritania
ΑU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HÜ	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	Π	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Кепуа	RO	Romania
CA	Canada	KG	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic	SD	Sudan
CG	Congo		of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SI	Slovenia
CI	Côte d'Ivoire	KZ	Kazakhstan	SK	Slovakia
CM	Cameroon	LI	Liechtenstein	SN	Senegal
CN	China	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
CZ	Czech Republic	LV	Latvia	TJ	Tajikistan
DE	Germany	MC	Monaco	TT	Trinidad and Tobago
DK	Demnark	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	US	United States of America
FI	Finland	ML	Mali	UZ	Uzbekistan
FR	Prance	MN	Mongolia	VN	Viet Nam
GA	Gabon		•		-

WO 95/05743 PCT/US94/08768

, ... i ji o

HIGH RATIO BAKING COMPOSITION

FIELD OF THE INVENTION

The invention generally relates to a high

5 ratio baking composition. More specifically, the
invention is directed to high ratio bakery mixes
including a heat treated soft flour, a non-flour fiber
and a water soluble heat denaturable protein useful for
preparation of baked goods including cakes, muffins, and
10 pancakes among other products.

BACKGROUND OF THE INVENTION

known in the baking industry. Flour treatment by

15 chlorine has been found to be necessary for the
production of baked products with the appropriate
volume, tenderness and handling properties such as, for
example, high quality cakes when using a high-ratio cake
formulation. A high ratio cake formulation is one in

20 which the weight ratio of sugar to flour in the cake is
between 1:1 and 1:1.4. The difference in concentration
of flour in the high ratio cakes as compared to sugar,
places a greater strain on the flour during the creation
of a cake structure.

25 If a high ratio cake is made from untreated flour, it appears to function quite normally in the earlier stages of batter development. Bell et al., J. Food Technol., 10, 147-156 (1975). The bubbles in the aerated batter expand, and the internal batter 30 temperature rises at a similar rate to batter made from chlorine-treated flour. Grider et al., Food Microstructure, 2, 153-160 (1983). Later in the baking process, differences in the performance of batters made from untreated and chlorine-treated flours begin to 35 appear. Batters formulated from untreated flour rise to a greater height than batters formulated from chlorinetreated flour. However, late in the bake the baked product formulated with the untreated batters falls more rapidly, and continues to fall as the baked good cools.

ن داميم الم

Russo et al., J. Food Technol., 5, 363-374 (1970); Frazier et al., Chemy Ind., 1008-1010 (1974); Cauvain, J. Sci. Food Agric., 26, 1861-1868 (1975).

Examination of the cake crumb structures has 5 revealed considerable differences in the sizes and appearances of the walls of the air cells in the crumb. Batters containing chlorine treated flours generally result in cakes having discrete, well-formed air cells with smooth cell walls, formed by starch granules 10 embedded in a continuous protein matrix. Grider et al., Food Microstructure, 2, 153-160 (1983). In contrast, cakes made with untreated flours have irregular, deformed air cells with ragged cell walls, in which the protein matrix appears to be partly disrupted. It is 15 believed that the smaller air cells are formed from the collapse of larger cells resulting in a new network of broken cells smaller in size than the original larger cells. Thus, it appears that the cell walls of a cake made from untreated flours are inherently weak and begin 20 to deform and collapse under the weight of the cake when the gas pressure dissipates from within the cell structure.

Additionally, there is evidence that some gas cells remain intact at the end of the bake, and are subsequently crushed by the external pressure when the water vapor within them condenses. This phenomenon would account for the accelerated collapse of the cake structure observed immediately after leaving the oven.

Thus, high ratio cake mixes have employed

30 chlorine-treated flour in their formulation. Although chlorine-treated flour has been used in Great Britain and the United States for many years, this use is not permitted in most of the Continental European countries. At the present time chlorine is permitted for use in

35 cake flour, but its continued use as a flour additive is in question because of safety concerns with the occupational use of chlorine and the safety of consuming chlorinated organic compounds in general. Hodge, Baking

وه رفستر ۱۰ مه

3

Industries Journal, July, page 14 (1975). There have been many attempts to formulate an acceptable alternative to chlorinated flour high ratio cakes.

Gough et al., CRC Critical Rev. in Food

5 Science and Nutrition, September, pp. 91-113 (1978),
disclose a review of the known alternatives to the
chlorination of flour including heat treating the flour.
See Russo et al., British Patent No. 1,110,771 and
Cauvain et al., J. Sci. Food Agric., 26, 1861-1868

10 (1975).

In Gough et al., a flour was heat treated at 200°C (392°F) for 6 minutes. Egg albumen was then added to increase the cake volume of the high ratio cake, but the organoleptic properties of the cake were undesirably changed. Thus, only a partial solution was provided.

These known alternatives to using chlorinated flour in a high ratio cake mix fail to perform as well as chlorinated flour high ratio cake mixes in terms of volume, density, fragility, and texture of the resulting cake. As a result, all high-ratio baking compositions produced commercially are made of and depend upon chlorinated flour. Thus, a substantial need exists for a high ratio baking composition in which the flour does not require treatment by chlorination.

25

SUMMARY OF THE INVENTION

The invention is directed to a high ratio baking composition without chlorinated flour equal in all respects to that made with chlorinated flour. In one aspect of the invention, there is provided a high ratio baking composition comprising a heat treated soft flour, sugar, an effective volume controlling amount of a non-flour fiber and an effective fragility controlling amount of a protein source.

In a preferred aspect, this invention relates to a high ratio cake composition comprising a heat treated soft wheat flour, sugar; about 0.25 to 3% by weight of a non-flour fiber and about 0.25 to 6% by

WO 95/05743 PCT/US94/08768

ns. 10 / 20 de

4

weight of a water soluble, heat denaturable protein wherein the heat treated soft wheat flour is prepared by the step comprising heating a soft wheat flour at a temperature greater than about 180°F for a sufficient amount of time to reduce the moisture content of the soft wheat flour to below about 10% by weight.

While not intending to limit the scope of the invention, it is believed that the moisture loss during the heat treating process indicates the amount of treatment the flour has undergone. It is unknown whether the moisture loss by itself is responsible for changes to the flour.

In a further aspect of the invention, there is provided a method of producing a high ratio baking

15 composition comprising the steps of preparing a heat treated soft flour and combining the heat treated soft flour, with a non-flour fiber, a water soluble, heat denaturable protein, and a sugar.

In an additional aspect of the invention,

20 there is provided a high ratio baked product prepared
from the high ratio baking composition prepared from the
method of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

25 The invention generally comprises high ratio baking compositions useful for the production of baked goods such as cakes with good volume and handling properties. The high ratio baking composition generally comprises heat treated soft flour, non-flour fiber and a 30 protein source. The high ratio baking composition of the invention has structural, organoleptic and handling characteristics comparable to those high ratio baking compositions utilizing chlorinated flour.

THE COMPOSITION

35 A. Heat Treated Flour

A principal constituent of the high ratio baking composition is heat treated flour. Flour generally occurs as either soft or hard flour. Soft flour is generally used in high ratio baking compositions. Soft flours are those which function to provide a more moist, more tender product with better organoleptic properties. Concomitantly, the function of the soft flour in a baked good is to provide structural rigidity.

Generally, any soft flour may be used in the invention. Sources of soft flour currently include, but should not be limited to, types of wheat. Importantly, 10 the soft flour of the invention has not, and will not, be treated with chlorine. Preferably, the composition of the invention will comprise a soft wheat flour.

Heat treatment of the soft flour functions to enhance the ability of the soft flour to provide a baked product with improved volume and structural strength. Generally, the heat treatment is performed on the soft flour at a sufficient temperature for a sufficient amount of time to effectively reduce the moisture level in the soft flour to about 5 to 10% by weight.

Preferably the moisture level in the soft flour is reduced to about 5 to 9% by weight, more preferably 5 to 7% by weight.

In general, the soft flour is not heated for too long or at too high of a temperature or for too long a time such that the soft flour would begin to scorch, caramelize, turn grey or otherwise decompose. The useful temperature and time ranges vary considerably. However, as a general rule, the higher the treatment temperature the less treatment time required. For example, the soft flour could be treated about 300°F to 600°F for about 0.1 to 45 seconds, or treated at about 100°F to 200°F for about 1 to 24 hours.

These general guidelines should serve to illustrate but not to limit the invention. It can be appreciated from these guidelines that heat treating the s ft flour too much will damage the soft flour, and heating the soft flour too little will not improve the function of the soft flour to the appropriate level.

In one embodim nt of the invention, the soft flour is heat treated by heating the soft flour to a temperature greater than about 180°F for a sufficient amount of time to reduce the moisture content in the soft flour to below about 10%.

Preferably, the heating of the soft flour is performed at a temperature greater than about 220°F. More preferably, the heating is performed at a temperature of about 240 to 250°F.

The heating may be performed at about 240 to 250°F for about 15 to 60 minutes. Preferably the heating is performed for about 30 to 60 minutes. More preferably the heating is performed for about 50 to 60 minutes.

Significantly, the heating is performed until
the moisture content of the soft flour is reduced to
about 5 to 10% by weight of the soft flour. During the
heat treatment of the soft flour, the soft flour is
modified in such a manner that a baked product from this
treated flour has improved volume compared to the nonheat treated soft flour. Preferably, the heating is
performed until the moisture content of the soft flour
is reduced to about 5 to 8% by weight of the soft flour
which produces a hygroscopic heat treated soft flour
with modified baking properties. More preferably, the
heating is performed until the moisture content of the
soft flour is reduced to about 5 to 7% by weight of the
soft flour.

After the heating is completed, the soft flour may be tempered to replace the moisture in the soft flour. Tempering is a process where the soft flour is spread out in a thin layer in a cabinet with humidity control and the flour absorbs moisture from the humidified air until the flour reaches the equilibrium moisture level.

Preferably, the soft flour is tempered until the moisture level in the soft flour is increased to about 10.5% and more preferably about 11 to 12% by

weight of the soft flour. Tempering the soft flour after completion of the heating of the soft flour functions to return the soft flour to about its original moisture level before the heating was performed.

In preparation of the baked good, the addition of too much of the heat treated soft flour generally results in a dry baked good which crumbles easily and has diminished mouthfeel. In contrast, the use of too little heat treated soft flour reduces the structural 10 integrity and volume of a baked good prepared from the high ratio baking composition of the present invention.

Generally, the high ratio baking composition of the present invention comprises about 20 to 45% by weight of the heat treated soft flour. Preferably the 15 high ratio baking composition comprises about 25 to 41% by weight of the heat treated soft flour. preferably, the high ratio baking composition comprises about 28 to 37% by weight of the soft wheat flour.

В. Fiber

5

The composition of the invention generally 20 also comprises a non-flour fiber. Fiber includes all food components that are not absorbed during digestion. Within the context of the invention, non-flour fiber means that this fiber component is from a fiber source 25 separate from and in addition to the fiber inherent in the heat treated soft flour. The addition of a nonflour fiber to the high ratio baking composition of the present invention is essential for obtaining baked volume, improved organoleptic properties and uniform 30 cell structure. Generally, fiber resulting from any number of materials may be used including non-flour fiber materials resulting from oats, rice, beans, peas, soybeans, nuts, barley, psyllium, gums, cotton seed, cellulose, sugar beet, fruit, figs, bran flakes, wheat, 35 broccoli, cabbage, green beans, brussels sprouts, radishes, cucumbers, green peppers, prunes, sweet potatoes, corn, cauliflower, apples, lentils, nuts, oranges and bananas, for example. In a preferred

embodiment of the invention, the non-flour fiber comprises an oat fiber.

In a typical embodiment of the invention, there is an effective volume controlling amount of a 5 non-flour fiber. Preferably the high ratio baking composition of the present invention comprises about 0.25 to 3% by weight of the non-flour fiber. More preferably, the high ratio baking composition comprises about 0.25 to 1.5% by weight of the non-flour fiber. 10 Most preferably, the high ratio baking composition comprises about 0.75 to 1.25% by weight of the non-flour Importantly, the addition of too much non-flour fiber into the high ratio baking composition, results in

a baked product which is dry and has poor mouthfeel.

15 C. Protein

30

In addition to heat treated soft flour and non-flour fiber, the high ratio baking composition of the invention may also comprise a protein source. Within the context of the invention, non-flour protein 20 means that this protein component is from a protein source separate from and in addition to the protein inherent in the heat treated soft flour. Sources of protein include, but are not limited to, vegetables, nuts, cereals, grains, legume, milk, as well as albumin 25 sources such as eggs, meat, fish, blood, collagen, gelatin and casein. Proteins function to reduce the fragility and enhance the handling properties of a baked good prepared from the high ratio baking composition of the invention.

Preferably, the protein is water soluble, and is heat denaturable during the baking process. Water soluble proteins are preferred in the high ratio baking compositions of the invention. The continuous liquid phase in a batter formed from the high ratio 35 compositions is water, and therefore, the proteins will be soluble and will become uniformly mixed or dissolved throughout the composition.

If a water soluble non-flour protein is not utilized, the protein may not be soluble in the high ratio baking compositions of the invention. This may result in less uniformity of the compositions.

Heat denaturable proteins polymerize and associate with other constituents during the baking process and are believed to form a gel network in the high ratio baked product. The network functions to provide adhesion or otherwise act as a glue to hold the 10 baked product together. This improves the handling properties.

Generally, any heat denaturable protein is useful in the composition of the invention. Preferably, the water soluble, heat denaturable protein is selected 15 from the group consisting of low temperature processed egg albumen, low temperature processed whey protein and mixtures thereof.

Generally, the protein may be present in the high ratio baking composition of the invention in the 20 form of a water soluble, heat denaturable protein in a concentration ranging from about 0.25 to 6 wt-% by weight of the solids in a batter prepared from the highratio baking composition, preferably from about 0.75 to 3 wt-% by weight of the solids in the batter, and most 25 preferably from about 0.75 to 1.5 wt-% by weight of the solids in the batter.

The addition of too much protein may result in a dry, tough baked good. In contrast, the addition of too little protein may result in a baked product which 30 is fragile and has poor handling properties.

D. Sugar

The high ratio baking composition may additionally comprise sugar. The sugar acts as a sweetener and bulking agent providing improved taste and 35 higher moisture mouthfeel in the baking composition. The sugar in the baking composition dissolves quickly upon consumption which provides a moist and tender mouthfeel. A high ratio baking composition is a

WO 95/05743 PCT/US94/08768

10

composition where the weight ratio of the sugar to heat treated soft flour is at least about 1 part sugar to 1 part heat treated soft flour and can be as high as 1.4 parts sugar to 1 part flour. Generally, the high ratio baking composition of the invention comprises sugar and heat treated soft flour wherein the ratio of sugar to heat treated soft flour is at least about 1 to 1. Preferably the ratio of sugar to heat treated soft flour is at least about 1.15 to 1. More preferably the ratio of sugar to heat treated soft flour is at least about 1.3 to 1.

The addition of too much sugar results in an insufficient amount of flour being present in the baking composition. Thus, a baked good prepared from a composition with too much sugar will collapse.

In contrast, too little sugar in the baking composition affords a baked good with poor taste and mouthfeel. The baked good has poor organoleptic properties because there is not enough sweetener in the baking composition. The baked product has a dry mouthfeel because there is an insufficient amount of sugar in the composition to have the tender or moist mouthfeel.

Illustrative examples of the above ratios

5 converted to weight percentages are shown below. The
table shows what the upper and lower amounts of sugar
that can be present in the high ratio baking composition
for each with respect to flour concentration.

Table 1

30	Wt-% Soft Flour	Suggested Lower Limit of Sugar Wt-%	Suggested Upper Limit of Sugar Wt-%
	20	20	28
35	30	30	42
	45	45	63

E. Additional Properties

The high ratio baking composition of the invention can optionally comprise a vari ty of materials to modify any number of organoleptic, nutritional,

flavor, color or other properties of a baked good resulting from the high ratio baking composition. In particular, the compositions can additionally include salt, bicarbonates, phosphates, gums, flavorings, starches, colorings, shortening, lecithin, food acids, oils, fats, milk, butter, and water.

F. Method of Preparation

A baked product prepared from the high ratio baking composition can be prepared by several known In one method, the oven is heated to 350°F. 10 procedures. Then two round pans measuring 8 inches in diameter are greased generously with shortening, margarine or butter and then lightly floured or sprayed with no-stick cooking spray. In a separate step, a dry high ratio 15 cake mix of the present invention, is mixed with water, oil and eggs in a large bowl at low speed until moistened. The baking composition is then beat for two minutes at high speed, and poured into the greased and floured pans. The pans containing the batter are then 20 placed in the preheated oven for 25 to 35 minutes. high ratio cake is done when a toothpick inserted in the center comes out clean or the high ratio cake springs back when lightly touched in the center. The high ratio cake is then removed from the oven and allowed to cool 25 in the pan on a cooling rack for 15 minutes. ratio cake can then be removed from the pan.

G. Formulations

The weight percentages throughout the invention including the formulations below are

30 calculated on a dry weight basis and do not include any water in the formulation. The weight percentages of the heat treated flour, non-flour fiber and sugar are calculated from the weight of the solids in the high-ratio baking composition. The weight percent of the solids in a batter made from the high-ratio baking compositions.

WO 95/05743 PCT/US94/08768

12

Table 2 (wt-%)

		<u>Useful</u>	Working	<u>Preferred</u>
5	Heat Treated Flour Fiber Protein Sugar	0.25 to 3	0.25 to 1.5 0.75 to 3	25 to 34 0.75 to 1.25 0.75 to 1.5 34 to 40

10 Density

The density of the high ratio baked products prepared from the high ratio baking compositions of the invention are comparable to baked products prepared with chlorinated flour. Preferably, the density of the high ratio baked product is less than about 5.6 to 6.3 g/in³. More preferably, the density of the high ratio baked product is about 5.2 to 5.9 g/in³, most preferably 4.8 to 5.5 g/in³.

20 <u>WORKING EXAMPLES</u>

The following working examples are provided to further illustrate the invention. However, these examples are not intended to be construed as limiting of the invention.

In the examples below, high ratio baking compositions were prepared using the specified components in each example below. Cakes were then baked utilizing the high ratio baking compositions of the examples. The "control" formulas in the examples below utilized chlorinated flour whereas the experimental formulas of the invention used only heat treated soft flour. Various characteristics of the baked products were then compared including: volume, moisture, fragility, mouthfeel and contour.

35

Volume Index

This procedure determines the volume indexes on baked cakes and muffins. The procedure is applicable to round, square, rectangular and loaf shaped cakes of different dimensions by proper setting and adjustment of the universal symmetry apparatus used.

A Universal Cake Symmetry Machine, manufactured by The Pillsbury Company Machine Shop, 300-2nd St., S.E., Minneapolis, Minnesota 55414 is utilized during the testing procedure.

5 Procedure

- 1. Place the empty pan in instrument.

 Calibrate equipment so that each of the three scales read "0" when the scale feet rest on the bottom of the pan. Be certain that the scale feet and the base of instrument are clean, and that the pans have flat bottoms (not bowed, bent, etc.)
- 2. The accuracy of the scale reading may then be checked by means of test blocks (or accurate ruler). The scale units are in sixteenths of an inch.
- 3. From the settings indicated on the table attached, select the proper machine type, and set back slide and both cams of the machine to the proper index markings.
- 4. Insert the proper jig into the base pan 20 cut out or use the stop where it is indicated in the table. If the machine model in use does not have a stop, prepare a jig to center the pan.
 - 5. As indicated in the table, insert the proper scale carriage stop adjusters into the scale carriage grooves on both sides.
 - 6. Cook the baked product to be tested as directed.
- 7. Place the product (in the pan) beneath the scale carriage and against the appropriate jig or 30 stop.
 - 8. Lower the scale carriage until the three scales nest on the product and the scale carriage nests on the stops (or on adjusters when used).
 - 9. Read the value on all three scales.
- Where the adjusters are used, add 20 to each scale value.
 - 10. Calculate the volume index.
 Volume Index = Sum of Scale Values on all 3 Scales

WO 95/05743 PCT/US94/08768

14

Example 1

Yellow Cake Formula

This example shows the volume effect that the heat treatment temperature has on the high ratio cakes which are treated for sixty minutes.

EXAMPLES

10	Treatment Temp.	1A 200°F (grams)	1B 225°F (grams)	1C 245°F (grams)
15	Mix Sugar Flour Shortening Additional Ingredients	233 193 55 48	233 193 55 48	233 193 55 48
20	<u>Add</u> Egg (whole) Oil Water	156 67 224	156 67 224	156 67 224
25	Resulting Product Volume Fragility Contour	79 fragile flat	83 fragile flat	88 fragile slight contour

Example 2

Yellow Cake Formula

5 This example shows the volume effect that the heat treatment time has on the high ratio cakes which are heat treated at about 245°F.

EXAMPLES

10	далигиоз					
	Treatment Times	2A 10 min.	2B 30 min.	2C 60 min.		
15 20	Mix Sugar Flour Shortening Additional Ingredients	233 grams 193 grams 55 grams 48 grams	233 grams 193 grams 55 grams 48 grams	233 grams 193 grams 55 grams 48 grams		
25	Add Egg (whole) Oil Water Resulting Product	156 grams 67 grams 224 grams	156 grams 67 grams 224 grams	156 grams 67 grams 224 grams		
	Volume Fragility Contour	83 fragile sunken	84 fragile flat	88 fragile slight contour		
30				CONCOUL		

WO 95/05743 PCT/US94/08768

16

Example 3

Yellow Cake Formula

5 This example shows the volume effect that varying oat fiber concentration has on the high ratio cakes below. The soft flour was heated at 245°F for 60 minutes.

10	EXAMPLES						
10		3 A	3B	3C			
	Oat Fiber	08	1%	3%			
	<u>Concentration</u>	(grams)	(grams)	(grams)			
15	Mix						
	Sugar	233	231	226			
	Flour	193	191	187			
	Shortening	55	54	53			
20	Additional Ingredients	48	48	47			
	Oat Fiber	-	5.3	15.9			
	<u>Add</u>			•			
	Egg (whole)	156	156	156			
25	Oil	67	67	67			
	Water	224	224	224			
	Resulting Product						
	Volume	90	95	99			
30	Fragility	Extremely fragile	Extremely fragile	Extremely fragile			
	Moistness	Moist eating quality	Moist eating quality	Slightly less moist eating quality			

Example 4

This example shows the volume effect that varying the protein concentration has on the high ratio cakes. The flour was a heat treated flour for about sixty minutes at about 245°F.

EXAMPLES

10	Protein Concentration	0% (grams)	1% (grams)
15	Mix Sugar Flour Shortening Additional Ingredients Oat Fiber Egg Albumin (dried)	231 191 54 48 5.3	228 189 54 48 5.3 5.3
20	<u>Add</u> Egg (whole) Oil Water	156 67 224	156 67 224
25	Resulting Product Volume Fragility	95 Extremely fragile	92 Excellent (equal to cakes made with chlorinated flour)

Working Example 5

Yellow Cake Formula

This example shows that a cake product of the invention can be prepared with similar properties to a cake product prepared from a chlorinated flour. A cake product formulated with unchlorinated flour (Example) was prepared and compared to a cake product formulated and prepared with a chlorinated flour product (control). The soft flour in the example was heated at 245°F for 60 minutes using a twin screw jacketed mixer, pressure rated to 50 p.s.i.g., such as model number CDB 0412FJD, manufactured by Custom Stainless Equipment Company, Santa Rose, California. The fiber used was Better Basic 780 White Oak fiber, available from D.D. Williamson & Company, Louisville, Kentucky.

20	Mix	<u>Control</u> (grams)	<u>Example</u> (grams)
25	Sugars Flour Shortening Additional Ingredients Oat fibers Egg Albumen (dried)	233 193 55 48 -	228 189 54 47 5.3 5.3
30	<u>Add</u> Egg (whole) Oil Water	156 67 224	156 67 224
35	Resulting Volume Contour Fragility Organoleptic Quality	90 index units excellent excellent excellent	93 index units excellent excellent excellent

Example 6

White Cake Formula

This example shows that a cake product of the invention can be prepared with similar properties to a cake product prepared from a chlorinated flour. A cake product formulated with unchlorinated flour (Example) was prepared and compared to a cake product formulated and prepared with a chlorinated flour product (control). The soft flour in the example was heated at 245°F for 60 minutes.

15	Mix	Control (grams)	<pre>Example (grams)</pre>
	Sugars	224	232
	Flour	217	225
	Shortening	48	49
20	Additional Ingredients	41	42
	Oat fibers	-	5.3
	Egg Albumen (dried)	-	1.3
	<u>Add</u>		
25	Egg (whites)	99	99
	Oil	51	51
	Water	290	290
	Resulting Volume	85 index units	87 index units
30	Contour	excellent	excellent
	Fragility	excellent	excellent
	Organoleptic Quality	excellent	excellent

Example 7

Chocolate Cake Formula

This example shows that a cake product of the invention can be prepared with similar properties to a cake product prepared from a chlorinated flour. A cake product formulated with unchlorinated flour (Example) was prepared and compared to a cake product formulated and prepared with a chlorinated flour product (control).

-							roer pro		, - (
	The soft	flour	in	the	example	was	heated	at	245	٥F	for
	60 minute	es.			•					_	

15	Mix	<u>Control</u> (grams)	<pre>Example (grams)</pre>
	Sugars Flour	200	197
		161	158
	Shortening	42	41
20	Additional Ingredients	119	117
	Oat fibers	_	5.2
	Egg Albumen (dried)	-	3.4
	<u>Add</u>		
25	Egg (whites)	156	156
	oii `	101	101
	Water	290	290
		230	230
	Resulting Volume	92 index units	92 index units
30	Contour	excellent	excellent
	Fragility	excellent	excellent
	Organoleptic Quality	excellent	excellent
		CUCCTTOTIC	CVCCTTGIIC

Example 8

Yellow Cake Formula

5 This example shows that there can be variation in the oil and water content of the compositions of the invention, Examples 8A and 8B, without losing the desired properties. A cake product formulated with a heat treated flour treated at about 245°F for about

10 60 minutes was prepared and compared to a cake product formulated and prepared with a chlorinated flour product (control).

EXAMPLES

15	ביים ביים ביים ביים ביים ביים ביים ביים				
	<u>Mix</u>	Control (grams)	8A (grams)	8B (grams)	
20	Sugar Flour Shortening Additional Ingredients	233 193 55 48	228 189 54 47	228 189 54 47	
25	Oat Fiber Egg Albumin (dried)	-	5.3 5.3	5.3 5.3	
30	<u>Add</u> Egg (whole) Oil Water	156 67 224	156 67 224	156 80 246	
	Resulting Volume Eating Ouality	90 Moist	90 Moist	87 Extremely moist	
35	Contour Fragility Organoleptic	excellent excellent	excellent excellent	excellent	
	<u>Ouality</u>	excellent	excellent	excellent	

While the invention has been specifically

described by reference to various embodiments, it will
be recognized that various modifications, adaptions and
variations, may be made without departing from the
spirit and scope of the invention as defined by the
following claims.

WE CLAIM:

- 1. A high ratio baking composition comprising:
 - (a) a chlorine free heat treated soft flour;
 - (b) an effective volume controlling amount of a non-flour fiber;
 - (c) an effective fragility controlling amount of a protein; and
 - (d) sugar

wherein the density of a baked product resulting from the high ratio baking composition is less than about 5.6 to 6.3 g/in^3 and the weight ratio of the sugar to the heat treated soft flour is at least about 1:1.

- 2. The composition of claim 1 wherein said heat treated soft flour is prepared by heating a soft flour to a temperature greater than about 180°F for a sufficient amount of time to reduce the moisture content in the soft flour to below about 10%.
- 3. The high ratio baking composition according to claim 2 wherein the soft flour is effectively tempered following the heating to increase the moisture in the soft flour to above about 10.5%.
- 4. The high ratio baking composition according to claim 1 wherein the soft flour comprises a soft wheat flour.
- 5. The high ratio baking composition according to claim 1 wherein the amount of non-flour fiber is about 0.25 to 3% by weight of the soft flour.
- 6. The high ratio baking composition according to claim 1 wherein the non-flour fiber comprises an oat fiber.

- 7. The high ratio baking composition according to claim 1 wherein the protein comprises a water soluble, heat denaturable protein.
- 8. The high ratio baking composition according to claim 7 wherein the amount of the water soluble, heat denaturable protein is about 0.25 to 6% by weight of the soft flour and the water soluble, heat denaturable protein is selected from the group consisting of egg albumen, whey and mixtures thereof.
- 9. A high ratio cake composition comprising:
 - (a) a chlorine free heat treated soft flour prepared by heating a soft flour to a temperature greater than about 220°F for a sufficient amount of time to reduce the moisture level in the soft flour to below about 8%;
 - (b) about 0.25 to 3% by weight of a non-flour fiber;
 - (c) about 0.75 to 3% by weight of a water soluble, heat denaturable protein; and
- (d) a sugar wherein the weight ratio of the sugar to the heat treated soft flour is at least about 1.15 to 1.
- 10. The high ratio cake composition of claim 9 comprising:
 - (a) a chlorine free heat treated soft flour prepared by heating a soft flour to a temperature of about 240 to 250°F for a sufficient amount of time to reduce the moisture level in the soft flour to about 5.5 to 7%;
 - (b) about 0.75 to 1.25% of a non-flour fiber by weight of the soft flour;
 - (c) about 0.75 to 1.5% of a water soluble, heat denaturable protein by weight of the soft flour; and
 - (d) a sugar

wherein the weight ratio of the sugar to the heat treated soft flour is at least about 1.3 to 1.

- 11. The high ratio cake composition according to claim 9 wherein the soft flour is effectively tempered following the heating to increase the moisture in the soft flour to above about 10.5%.
- 12. The high ratio cake composition according to claim 9 wherein the non-flour fiber comprises an oat fiber.
- 13. The high ratio cake composition according to claim 9 wherein the water soluble, heat denaturable protein is selected from the group consisting of egg albumen, whey protein, soy protein and mixtures thereof.
- 14. A baked product resulting from the high ratio baking composition of claim 1.
- 15. A cake product resulting from the high ratio composition of claim 9.
- 16. A method of preparing a high ratio baking composition comprising the steps of:
 - (a) preparing a chlorine free heat treated soft flour; and
 - (b) combining the heat treated soft flour with an effective volume controlling amount of a non-flour fiber and an effective fragility controlling amount of a protein.
- 17. The method of claim 16 wherein the heat treated soft flour is prepared by heating a soft flour to a temperature greater than 180°F for a sufficient amount of time to reduce the moisture content in the flour to below about 10%.

- 18. The method of claim 16 further comprising the steps of tempering the soft flour following the heating to increase the moisture in the soft flour to above about 10.5% by weight.
- 19. A method of preparing a high ratio cake composition comprising the steps of:
 - (a) preparing a chlorine free heat treated soft flour by heating a soft flour to a temperature greater than about 220°F for a sufficient amount of time to reduce the moisture level in the soft flour to below about 8%; and
 - (b) combining:
 - (i) the heat treated soft flour:
 - (ii) about 0.75 to 3% by weight of a
 water soluble, heat denaturable, non-flour
 protein;
 - (iii) about 0.25 to 3% by weight of a non-flour fiber; and
 - (iv) a sugar

wherein the weight ratio of the sugar to the heat treated soft flour is at least about 1.15 to 1.

- 20. The method of claim 19 further comprising the steps of tempering the soft flour following the heating to increase the moisture in the soft flour to above about 10.5% by weight.
- 21. The method of preparing a high ratio cake composition according to claim 19 wherein the chlorine free heat treated soft flour is prepared by heating a soft flour to a temperature of about 240 to 250°F for a sufficient amount of time to reduce the moisture level in the soft flour to about 5.5 to 7%, and the composition comprises: the heat treated soft flour; about 0.75 to 1.25% of a non-flour fiber by weight of the soft flour; about 0.75 to 1.5% of a water solubl, heat denaturable protein by weight of the soft flour;

and a sugar wherein the weight ratio of the sugar to the heat treated soft flour is at least about 1.3 to 1.

- 22. A cake product comprising a high ratio baking composition prepared according to the method of claim 16.
- 23. A cake product prepared according to the method of claim 19.

INTERNATIONAL SEARCH REPORT

Int. .onal Application No PCT/US 94/08768

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A21D6/00 A21D13/02 According to International Patent Classification (IPC) or to both national classification and IPC **B. PIELDS SEARCHED** Minimum documentation searched (classification system followed by classification symbols) IPC 6 A21D Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practical, search terms used) C. DOCUMENTS CONSIDERED TO BE RELEVANT Category * Citation of document, with indication, where appropriate, of the relevant passages Relevant to claim No. Y US,A,3 428 461 (W. A. HATTON ET AL.) 18 February 1969 7-10, 13-17, 19-23 see claim 1; examples Y GB, A, 1 499 986 (J. LYONS AND COMPANY LTD) 1-4, 1 February 1978 7-11. 13 - 23see page 4, line 111 - line 116; claims; examples US,A,2 525 599 (E. G. GUSTAVSON) 10 Υ 1-23 October 1950 see column 2, line 47 - column 3, line 18; claims Further documents are listed in the continuation of box C. Patent family members are listed in annex. Special categories of cited documents: To later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the "A" document defining the general state of the art which is not considered to be of particular relevance invention "E" earlier document but published on or after the international "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "O" document referring to an oral disclosure, use, exhibition or other means document published prior to the international filing date but later than the priority date claimed "&" document member of the same patent family Date of the actual completion of the international search Date of mailing of the international search report 1 4, 12, 94 21 November 1994 Name and mailing address of the ISA Authorized officer European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Coucke, A Fax (+31-70) 340-3016

Form PCT/ISA/210 (second sheet) (July 1992)

1.

INTERNATIONAL SEARCH REPORT

Int. ional Application No PCT/US 94/08768

		PC1/US 94/08/68
C.(Continua Category *	tion) DOCUMENTS CONSIDERED TO BE RELEVANT Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Category	Citation of Execution, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE,A,24 42 552 (FLOUR MILLING AND BAKING RESEARCH ASSOCIATION) 13 March 1975 see claims; examples	1-23
Y	WO,A,91 19421 (KRAFT GENERAL FOODS INC.) 26 December 1991 see claims 2,11	1-23
Y	EP,A,O 552 006 (CONAGRA INC.) 21 July 1993 see claims 1,9-13; examples 22-24; table 11B	1-23
A	PATENT ABSTRACTS OF JAPAN vol. 12, no. 242 (C-150) 8 July 1988 & JP,A,63 032 455 (NITTO SEIFUN KK) 12 February 1988 see abstract	1-23
	 -	
	•	
		•
1		
	•	
İ		
İ		

1

INTERNATIONAL SEARCH REPORT

Information on patent family members

In: ional Application No
PCT/US 94/08768

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-3428461	18-02-69	NONE	
GB-A-1499986	01-02-78	NONE	
US-A-2525599		NONE	
DE-A-2442552	13-03-75	GB-A- 1444173 CA-A- 1028193 NL-A- 7411906 US-A- 3974298	21-03-78 11-03-75
WO-A-9119421	26-12-91	EP-A- 0533668 EP-A- 0538253 WO-A- 9119423 US-A- 5133984 US-A- 5336515	28-04-93 26-12-91 28-07-92
EP-A-0552006	21-07-93	AU-A- 3114893 CA-A- 2087047 JP-A- 5244856 US-A- 5352473	14-07-93 24-09-93